




2KSDI Lens Selection Guide



Sensor Comparison	
35mm Full Frame	
Super-35 Film	
2KSDI	
Format	Crop Factor
35mm Full Frame	3.15 : 1
Super-35 Film	2.25 : 1

2KSDI Output Format	Image Circle Diameter	Lens Format
2048 x 1080	 12.7mm	≥1 inch recommended
1920 x 1080	 12.1mm	≥1 inch recommended, or generous 2/3 inch
1280 x 720	 8.1mm	≥1/2 inch recommended


Manual C-Mount Lenses

Features

- Light weight and compact size
- Wide angles with minimal distortion
- Industrial construction with quality optics
- Manual adjustment of focus, iris, and zoom

Lens Manufacturers

- Kowa Optimed, Schneider Optics, etc.



Motorized C-Mount Lenses

Features

- Best solution for remote control of focus, iris and zoom
- Dedicated remote lens controllers allow coarse and fine adjustment
- Light weight and compact size

Lens Manufacturers

- Fujinon, Resolve Optics (distributed by Polecam)



EF and EF-S Lenses

Features

- 2KSDI EF-Mount kit allows mounting and control for EF/EF-S lenses
- Kit includes mounting adapter and camera interface unit
- Remotely adjust focus and iris using 2KSDI handheld remote
- Lenses provide ample coverage of 2KSDI sensor

Lens Manufacturers

- Canon, Zeiss, Sigma, Rokinon, etc.



Adapters for Other Lenses

Features

- Several C-mount adapters available for different lens mount types
- Passive adapters are low-cost (no active control of motorized lenses)
- Lenses provide ample coverage of 2KSDI sensor
- Make use of your existing lenses

Adapter Manufacturers

- MTF Services, Visual Products, Edmund Optics, etc.

PL-mount
B4-mount
F-mount
K-mount



1510 Woodcock Street Unit 12, London, ON, Canada N6H 5S1
Tel: +1 519 663 9570 Fax: +1 519 663 9571 info2@ioindustries.com

www.ioindustries.com

Copyright© 2013 IO Industries Inc. Flare is a trademark of IO Industries.
All other trademarks are the property of their respective owners.

IOI
IO INDUSTRIES